

MATERIAL SAFETY DATA SHEET

Date : Jan/10/2011

1. Identification of the substance/preparation and of the company/undertaking

Identification of the product

Product name : Li-FeS₂ Battery
Chemical System: Lithium and Iron Disulfide
Model: Cylindrical Type Cells_
Designated for 'DO NOT RECHARGE'? Yes No

Manufacturer/supplier identification

Company : Great Power Battery Co., Ltd.
Contact for information : 922 Xicun Section, Shiliang Road, Shawan, Panyu,
Guangzhou, GD, PRC
Emergency telephone No. : 0086-20-61920399

2. Composition/information on ingredients

Ingredient	Percent	CAS Index No./EC No.	Molar mass	Molecular formula	Symbol
Iron Disulfide	34.4%	1309-36-0		FeS ₂	
Lithium	6.2%	7439-93-2		Li	
Organic Solvent	14.8%	N/A			
Lithium Salt	1.6%	N/A			
Polypropylene	2.3%	N/A			
Steel	32.9%	7439-89-6		Fe	
Aluminum	7.8%	7429-90-5		Al	

Remark: The weight of metallic lithium per cell is <0.90 g.

3. Hazards identification

Routes of Entry:

Inhalation - Yes
Skin - Yes
Ingestion - Yes

Health Hazards (Acute and Chronic):

These chemicals are contained in a sealed can. Risk of exposure occurs only if the battery is mechanically or

electrically abused. The most likely risk is an acute exposure when the gas release vent works. Organic solvent has slight toxicity and can irritate skin and eyes. Lithium salt is irritating to skin, eyes and mucous membranes and should be avoided.

Carcinogenicity:

NTP: None IARC Monograph: None OSHA Regulated: None

Medical Conditions Generally Aggravated by Exposure:

An acute exposure will not generally aggravate any medical condition.

4. First aid measures

After skin contact :	In case of skin contact with contents of battery, flush immediately with water. If irritation persists, get medical help.
After eye contact :	For eye contact, flush with copious amounts of water for 15 minutes. Do not inhale leaked material. If irritation persists, get medical help.

5. Fire-fighting measures

Extinguishing Media: CO₂ or dry chemicals

Flammable Limits: Not available

6. Accidental release measures

The preferred response is to leave the area and allow the batteries to cool and the vapors to dissipate. Avoid skin and eye contact or inhalation of vapors. Remove spilled liquid with absorbent and incinerate.

7. Handling and storage

Avoid mechanical or electrical abuse. Batteries may explode or cause burns, if disassembled, crushed or exposed to fire or high temperatures. Do not short or install with incorrect polarity.

8. Exposure controls/personal protection

Specific control parameter :

Personal protective equipment :

Respiratory protection (Specify Type) :	Not necessary under conditions of normal use.
Ventilation:	Not necessary under conditions of normal use.
Protective Gloves:	Not necessary under conditions of normal use.
Eye protection:	Not necessary under conditions of normal use.
Other Protective (Clothing or Equipment):	Not necessary under conditions of normal use.

9. Physical and chemical properties

Specific Gravity: (H₂O=1): FeS₂: 6.66

Melting Point: (°C): FeS₂ decomposes at 1193 deg. C

FeS₂ is a brass-colored, odorless mineral powder.

Lithium is a soft, silvery metal.

Organic solvent is an odorless, colorless or light yellow liquid.

Lithium salt is a white, crystalline and odorless powder.

10. Stability and reactivity

Stability: Stable

Conditions to Avoid: Do not heat, disassemble or charge.

Hazardous Decomposition or By-products: N/A

Hazardous polymerization will not occur.

11. Toxicological information

Acute toxicity :

Organic solvent

Further toxicological information :

Lithium

12. Ecological information

Ecotoxic effects : N/A

Further ecological data : N/A

13. Disposal considerations

Great Power encourages battery recycling. Our Li-FeS₂ batteries are recyclable through the Rechargeable Battery Recycling Corporation's (RBRC) *Charge Up to Recycle! Program*. For information call 1-800-8-BATTERY or

